

TECHNICAL DATA SHEET

GASIR® Infrared Lens 18 mm f/1.0

Umicore's GASIR[®] infrared lenses have been developed for an easy fit with a wide range of camera cores. Our catalog lenses provide a cost-effective solution for high-resolution thermal imaging and sensing applications.

This lens may be offered with other coating variants upon request. Its **lightweight and cost-effective design** makes it a prime choice for your application.

This lens is compatible with 12 µm VGA detectors and smaller.



OPTICAL SPECIFICATIONS

Effective focal length 18.0 mm Radiometric f-number f/1.06 Waveband $8-12 \mu m$ Maximum field of view $25^{\circ} \times 19.1^{\circ}$ Image circle 10.0 mm

Fields of view (HFOV \times VFOV)

Detector pixel pitch	Detector format		
	160 × 120	320 × 240	640×480
12 µm	6.1° × 4.6°	$12.2^{\circ} \times 9.2^{\circ}$	24° × 18.3°
17 µm	8.7° × 6.5°	$17.3^{\circ} \times 13.0^{\circ}$	

Other detectors may be possible. Please contact us for more information.

LENS VARIANTS

Mechanical variant	Fixed Focus	
Mechanical interface	12 μm mount M24	
Coating option	LWP	
Part number	18058_100	

COATING OPTIONS

	Transmission*	Lens coatings	Comments
LWP	> 89%	LWP on one internal surface HEAR on all other surfaces	Sunlight filter coating for use with uncoated detectors.

HEAR: High Efficiency Anti-Reflection; LWP: Long Wave Pass

Additional specifications are provided in the coatings Technical Data Sheets available on our website.

^{*}average transmission over waveband



GASIR® Infrared Lens – 18 mm f/1.0

Fixed Focus

	Part Number LWP 18058_100	
Focus range	0.4 m to ∞ with 0.67 mm refocus	
Operating temperature	-40 °C to +80 °C	
Storage temperature	−57 °C to +105 °C	
Weight	25 g	
Housing material	Black anodized aluminium	

^{*}dimensions valid with 0.63 mm Si detector window

