

# Diamond Like Carbon

## 8μm-12μm

UCS\_GE\_03\_DLC

**Productnumber:** 2Ge000003

This is an extremely rugged and abrasion resistant anti reflection coating for use in the 8-12μm waveband. These properties make it ideal for external surface applications where extreme environmental conditions will be encountered such as marine environments.

It is normally used in conjunction with a high efficiency anti-reflection coating (UCS\_GE\_01) on the second surface.



## Spectral - additional

Transmission (Average)	>89% 8μm-12μm	For a 1mm thick witness piece, coated one side UCS_Ge_03 and one side UCS_Ge_01.
Reflection (Average)	<3% 8μm-12μm	Per surface, from a single side coated 1mm thick witness piece, coated with UCS_Ge_03
Angle of Incidence	0°-20°	

## Environmental Properties

Adhesion	MIL-C-48497A, 08/09/1980, para 4.5.3.1
Adhesion Remark	Tape Test
Humidity	MIL-C-48497A, 08/09/1980, para 4.5.3.2
Humidity Remark	24Hrs, 49°C, 95-100% relative humidity
Abrasion	MIL-C-48497A, 08/09/1980, para 4.5.5.1
Abrasion Remark	Severe, 20 Strokes Eraser
Salt spray	MIL-C-675C, 22/08/1980, para 4.5.9
Salt spray Remark	200hrs salt spray fog exposure
Salt Soln	MIL-C-48497A, 08/09/1980, para 4.5.5.2
Salt Soln Remark	24hrs immersion in salt water
Solubility	TS1888, 01/07/1979, para 5.2.2.1
Solubility Remark	28 days immersion in water

# Environmental - additional

Wiper Test	TS1888, 01/07/1979, para 5.4.3	10,000 wipes with windscreen wiper in water/sand slurry.
------------	--------------------------------	--

## Sizes

Up to 275mm diameter

