

**GASIR® Infrared Lens
FL 75 mm f/1.1**

Fixed focus

Introduction



Umicore's GASIR® infrared lenses have been developed for an easy fit with a wide range of camera cores. Our catalog lenses provide a cost-effective solution for high-resolution thermal imaging and sensing applications.

This **athermalized lens** offers superior performance from -40 °C to +80 °C. Its **lightweight and intuitive design** make it a prime choice for your application. This lens is compatible with **17 µm VGA** detectors and smaller.

Optical Specifications

Focal length	75.0 mm
Aperture-based f-number	f/1.12
Waveband	8-12 µm
Transmission	> 87% average over waveband
Focus range	30 m to infinity with 0.19 mm refocus
Assembly weight	259 g

Field of view

640 x 512	17 µm		8.1° (H) x 6.5° (V) - 10.1° (diagonal)
640 x 480	17 µm	VGA	8.1° (H) x 6.1° (V) - 9.9° (diagonal)
640 x 480	12 µm	VGA	5.8° (H) x 4.4° (V) - 7.2° (diagonal)
384 x 288	17 µm	qVGA+	4.9° (H) x 3.7° (V) - 6.1° (diagonal)
320 x 240	17 µm	qVGA	4.1° (H) x 3.1° (V) - 5.1° (diagonal)
320 x 240	12 µm	qVGA	2.9° (H) x 2.2° (V) - 3.6° (diagonal)

Environmental Specifications

Operating temperature	-40 °C to +80 °C
Storage temperature	-57 °C to +105 °C
Vibration	MIL-STD-810E Method 514.4 Proc I Cat 8
Mechanical shock	MIL-E-5400T
Solar radiation	MIL-STD-810G Method 505.5
Sealing	IP67

Front surface
Internal surfaces

iDLC @ 8-12 μm
High efficiency anti-reflective coating @ 8-12 μm

Assembly & Interface Specifications

Black anodized aluminium

Image plane-related dimensions valid with 1 mm Ge detector window (not included)

